



U, U3	= Standard Ballast
UE3, U3E3	= Standard Ballast (347V)
U2MX1	= Mark X Dimming 26W, 120V*
U2MX2	= Mark X Dimming 26W, 277V*
U4MX1	= Mark X Dimming 32/42W, 120V*
U4MX2	= Mark X Dimming 32/42W, 277V*
UMX1	= Mark X Dimming 57W, 120V*
UMX2	= Mark X Dimming 57W, 277V*

Complete fixture consists of Reflector, Power Head, Deco Kit, Deco Disk and Suspension. Select each separately.

*Not compatible with 2x57W

* Use with Standard Cord or Deco Suspension Kit.
** DALI requires a 5-wire suspension.

Note: See specification sheet 412DK for more information on suspension, Disks & Support Arms

	General Electric	Osram/Sylvania	Philips
(2) 26W Triple Tube 4-Pin (Amalgam) Compact Fluorescent Lamp	F26TBX/*A/4P	CF26DT/E/IN/*	PL-T26W/*4P
(2) 32W Triple Tube 4-Pin (Amalgam) Compact Fluorescent Lamp	F32TBX/*A/4P	CF32DT/E/IN/*	PL-T32W/*4P
(2) 42W Triple Tube 4-Pin (Amalgam) Compact Fluorescent Lamp	F42TBX/*A/4P	CF42DT/E/IN/*	PL-T42W/*4P
(2) 57W Triple Tube 4-Pin (Amalgam) Compact Fluorescent Lamp	F57OBX/*A/4P/EOL	CF57DT/E/IN/*	N/A

Notes:

HIGHTOLIER®